



ISO 4028  
UNI 5925  
DIN 915



CON ESTREMITA' CILINDRICA

**VITI SENZA TESTA CON ESAGONO INCASSATO**

**45 H**

d	3	4	5	6	8	10	12	14	16
P.G.	0,5	0,7	0,8	1	1,25	1,5	1,75	2	2
t	2,5	3	3,5	4	5	6	8	8	10
y	2	2,5	3,5	4	5,5	7	8,5	10	12
k									
z	2,5	3	3	3,5	5	5,5	7	7	9
s	1,5	2	2,5	3	4	5	6	6	8

L = lunghezza in mm.

**Prezzo base in €uro per 100 pezzi**

4	5,40								
5	5,40	5,40	7,55						
6	5,65	5,00	5,40	9,40					
8	5,80	5,25	5,40	6,05					
10	6,45	5,40	5,65	6,20	8,10				
12	7,25	5,90	6,20	6,75	8,50	16,15			
14	10,25	8,10	7,95	8,35	11,45	17,50			
16	10,25	8,10	7,95	8,35	11,45	17,50	30,10	64,50	64,50
20	12,35	9,40	10,50	10,30	13,45	19,35	34,95	67,15	67,15
25	13,85	13,45	14,30	13,95	17,20	23,70	40,85	73,90	73,90
30	18,30	15,60	16,15	17,50	20,15	28,20	49,70	83,30	83,30
35		19,00	20,45	20,70	24,45	32,25	53,75	94,00	94,00
40		22,05	22,35	22,85	28,20	34,95	63,40	98,05	98,05
45			25,60	25,30	32,75	45,70	68,00	111,50	111,50
50			30,00	28,20	38,95	52,40	98,05	119,55	119,55
60					48,35	92,70	120,90	155,80	155,80
70					80,60	114,15	161,15	182,65	182,65