



ISO 7050
UNI 6955
DIN 7982



**VITI AUTOFILETTANTI TESTA SVASATA PIANA CON IMPRONTA A CROCE
ZINCATE**

d₁	2,2	2,9	3,5	3,9	4,2	4,8	5,5	6,3	
D	max.	4,3	5,5	6,8	7,5	8,1	9,5	10,8	12,4
	min.	4	5,2	5,44	7,14	7,74	9,14	10,37	11,97
k	1,3	1,7	2,1	2,3	2,5	3	3,4	3,8	
r	0,8	1,1	1,4	1,5	1,6	1,9	2,1	2,4	
inserto n.	1	1	2	2	2	2	3	3	
m	2,6	3	4,2	4,4	4,6	5	6,5	7,1	
profondità	max.	1,32	1,8	2,03	2,26	2,46	2,87	3,15	3,66
	min.	0,86	1,35	1,4	1,63	1,8	2,26	2,49	3

L = lunghezza in mm.

Prezzo base in €uro per 100 pezzi

4,5								
6,5	1,32	0,98	1,24					
9,5	1,35	0,99	1,13	1,29	1,48			
13	1,47	1,06	1,19	1,37	1,58	2,19		
16	1,76	1,12	1,29	1,49	1,72	2,36	3,82	5,11
19		1,25	1,39	1,64	1,85	2,57	4,26	5,69
22		1,46	1,73	2,05	2,15	2,87	4,86	6,41
25		1,50	1,80	2,13	2,34	2,95	5,21	6,89
32		2,48	2,29	2,66	3,03	3,98	6,77	8,91
38		3,75	2,76	3,44	3,84	4,56	7,42	10,04
45			4,21	4,70	5,21	6,18	9,38	12,29
50			5,62	6,30	7,01	7,96	10,81	13,54